

Strategy for the real-time detection of thermal events on the plasma facing components of Wendelstein 7-X

A. Puig Sitjes¹, M. Jakubowski¹, J. Fellingner¹, P. Drewelow¹, Y. Gao¹, H. Niemann¹, T.S. Pedersen¹, R. König¹, D. Naujoks¹, A. Winter¹, H. Laqua¹, S. Dumke¹, V. Moncada², C. Belafdil², R. Mitteau², M.H. Aumeunier², F. Pisano³, E. Aymerich³, B. Cannas³, G. Kocsis⁴, T. Szepesi⁴, G. Cseh⁴, T. Szabolics⁴, J.R. Casas⁵, J.R. Morros⁵, P. Salembier⁵, R. Clemente⁵, M. Cobos⁵, I. Caminal⁵, A. Palacios⁵, A. Moreno⁵, S. Quiceno⁵ and the W7-X Team.

¹Max-Planck-Institut für Plasmaphysik, Wendelsteinstraße 1, Greifswald 17491, Germany.

²CEA, IRFM, Saint Paul-lez-Durance F-13108, France.

³University of Cagliari, Piazza d'Armi, Cagliari 09126, Italy.

⁴Centre for Energy Research, H-1121 Budapest, Konkoly Thege 29-33, Hungary.

⁵Universitat Politècnica de Catalunya, Jordi Girona 1-3, Barcelona 08034, Spain.

Abstract

Wendelstein 7-X (W7-X), as the most advanced fusion experiment in the stellarator line, aims at demonstrating the feasibility of the stellarator concept as a future fusion power plant. It is planned to restart operation by the end of 2021 with a high heat flux divertor and water-cooled plasma facing components (PFCs) to demonstrate steady-state operation. With increasing plasma energy limits from 1GJ to 18GJ, the PFCs have to be protected from overheating with a fully autonomous system, able to prevent damage to the machine when a dangerous thermal event is detected.

During the past operation phase OP1.2, which ran with inertially cooled test divertor units, extensive experience was gained with the preliminary design of the thermal event detection system [1]. By then, the system was not yet real-time capable and it was not fully automated, requiring manual supervision between discharges. This experience, however, allowed to prove the validity of some design concepts and to define the new strategy towards the protection of the machine in steady-state operation, when the system will be connected to the Interlock System and the feedback control.

In this work, the design of the real-time thermal event detection system for W7-X for steady-state operation is presented. The system is based on the thermography and video diagnostics to monitor the divertor units, the baffles and the wall heat-shields and panels. It will be implemented on a real-time distributed system and integrated in CoDaC's safety infrastructure. The system relies on computer vision and machine learning techniques to perform a spatio-temporal analysis to detect and classify the thermal events and to perform a risk evaluation. The results and the main conclusions drawn from the analysis of the data from the past campaign are reported.

[1] A. Puig Sitjes et al., *Wendelstein 7-X Near Real-Time Image Diagnostic System for Plasma-Facing Components Protection*, Fusion Science and Technology, Vol. 74, issue 1-2, 2018.